



Product Survey Questionnaire

Existing Facility ; New Construction ; Door Opening Size: ____" Wide x ____" High; Dock Height: ____"

Driveway Composition: Concrete ; Asphalt ; Other _____

Driveway Approach: Level ; Decline __% ; Incline __%

Building Wall Material: Tilt-up ; Brick or Block ; Metal Siding

Dock Face Material: Poured Concrete ; Tilt-up ; Concrete Block Dock Edge Steel

Dock Edge Steel Dimensions, (if applicable): _____

Products to be furnished:

Dock Levelers: Pit Type ; Edge-of-Dock Mechanical ; Hydraulic

Size: _____; Capacity: _____; Model (if known): _____

Dock Seals or Shelters:

Compression Seal ; "L" Shaped Seal ; Soft-sided Shelter ; Rigid Shelter ; Flexible Shelter ; Rail Shelter

Base Fabric: 50oz, AB500 ; 22oz Vinyl ; 40oz Vinyl ; 16oz Hypalon ; 40oz Hypalon

Wear Pleats (seals only): 4" ; 8" ; 16" Fabric: _____ (see above)

Inside Half-wrap (seals only) Fabric: _____ (up approx. 48" - see above)

Side Frame Cover (shelters only): Std. 32oz White Flexible Vinyl ; 6 oz Translucent Fiberglass

Dock Bumpers: Molded ; Laminated: Horizontal ; Vertical ; Size ____" Deep x ____" High x ____" Long

Special: _____

(I.E. Steel-faced, Flexsteel, Special Anchors)

Truck Restraints:

Automatic w/ Push-button Control (includes signs & automatic lights)

Manual: Signs Only ; Signs & Manual Lights ; Signs & Automatic Lights

Metal Hoods: Projection ____"; Width ____"; Length ____' (10' standard)

Dock Lights: Arm Length – 24" ; 40" ; 60"

Wheel Chocks: Molded Rubber ; Laminated ; Aluminum

Optional Chain - 10' ; 15' ; Optional Handle (molded rubber only)

Truck Information for typical truck / trailer (check all that apply):

Standard Box ; Refer ; Flat Bed ; Step-deck ; ISO Container ; Air Ride

Specialty Trucks: Step-van ; UPS ; Other (please indicate) _____

Height from Ground to: Top of Trailer ____"; Bed of Trailer ____"; ICC Bar ____"

Width of Trailer: 96" ; 102" ; Other ____"; Doors: Swing Open ; Roll-up

Trailer Placement: Yard Jockey Yes or No