

DOCK EQUIPMENT QUESTIONNAIRE

END USER / JOB NAME: _____

Basic Building Information (Please check & complete all that apply):

Existing Facility ; New Construction ; Addition

Driveway Details: Level ; Decline __%; Level-off at Bottom of Decline ____"; Incline __%;

Trench Drain (*Most applicable with ground mounted trailer restraints - Details add separate sheet*)

Driveway Composition: Concrete ; Asphalt ; Other Specify: _____.

Building Wall Material: Tilt-up ; Brick ; Block ; Metal Siding ; Other , specify _____.

Dock Face Material: Poured Concrete ; Tilt-up ; Concrete Block

Dock Edge Steel: No ; Yes Dimensions: _____.

Dock Height: _____"

Information for Typical Truck / Trailer:

Box Truck ; Dry Van ; Refer ; Flat Bed ; Step-deck ; ISO Container ; Air Ride

Specialty Trucks: Step-van ; UPS ; Other, specify: _____.

Height from Ground to: Top of Trailer ____"; Bed of Trailer ____"; Rear Impact Guard ____"

Width of Trailer: 96" ; 102" ; Other, specify: ____"; Doors: Swing Open ; Roll-up

Length of Truck / Trailer: 20' ; 24' ; 48' ; 53' ; Other , Specify: ____'

Trailer Placement: Standard Tractor ; Yard-spotter Tractor

PRODUCTS TO BE QUOTED (Please check & complete all that apply):

Dock Leveler - Pit Type: Mechanical ; Hydraulic

Hydraulic Motor: 1ph -115v ; 230v / 3ph – 208-230v ; 480v/3ph

Pit Dimensions: ____" Width x ____" Length x ____" Depth (Measure Concrete Opening)

Model Size: _____; Capacity: _____; Model (if known): _____.

Edge-of-Dock Leveler: Mechanical ; Hydraulic

Hydraulic Motor: 1ph -115v ; 230v / 3ph – 208-230v ; 480v/3ph

Standard Mount ; Recessed Mount Pit Dimensions: ____" Width x ____"; Length x ____" Depth

(Note: For Recessed Mount, Measure Concrete Opening)

Size: _____; Capacity: _____; Model (if known): _____.

Leveler, Hydraulic Vertical Storing ('HVS' Series):

Hydraulic Motor: 1ph -115v ; 230v / 3ph – 208-230v ; 480v/3ph

Pit Dimensions: ____" Width x ____" Length x ____" Depth (Measure Concrete Opening)

Continuous Pit ; Individual Pit

PRODUCTS TO BE QUOTED, cont. (Please check & complete all that apply):

Leveler, Hydraulic Rail Vertical Storing ('RVS' Series) - Special Survey Form Required:

Hydraulic Motor: 1ph -115v ; 230v / 3ph – 208-230v ; 480v/3ph

Mount Type: Fixed ; Track

Rail Car Width: Min ___' ___"; Max ___' ___"; (Can accommodate various rail car widths from 9' 4" to 10' 8")

Distance From Dock Face to Φ (Centerline) of Track ___' ___"

Top of Rail to Dock Height ___"

Trailer Restraints (All Come Equipped with Driver Warning Signs):

Automatic with Push-button Control & Automatic LED Lights

Mechanical with Manual Lights ; Automatic LED Lights

Dock Bumpers: Molded / Laminated: Horizontal ; Vertical

Size: ___" Depth x ___" Height x ___" Length

Special: _____

(i.e. Steel-faced, Flexsteel™, Special Anchors)

Wheel Chocks: Molded ; Handle (molded only); Laminated ; Aluminum ; Chain: 10' ; 15'

Dock Lights:

Single Arm: 40" ; 60" / Double Arm: 24" ; 40" ; 60" ; 90" ; 114"

Double Strut Swing Arm: 24" ; 40" ; 60" ; 90" ; 114"

Double Strut Flex Arm: 24" ; 40" ; 60" ; 90"

Stop & Go Lights: SG10 (Drone) ; SG20 (Indoor with Toggle Switch) ; SG30 (Indoor/Outdoor)

Dock Seals & Shelters:

Dock Seals: Compression Seal ; 'L' Shaped Seal

Truck Shelter: Rigid: ; Flexible ; Inflatable ; Soft-sided

Rail Shelter-Flexible: ; 3 Sided ; 4 Sided

Rail Shelter-Inflatable: ; 3 Sided ; 4 Sided

Door Opening: ___" Width x ___"; Height

Dock / Wall Construction: Flush ; Wall Set-back _____"; Cantilevered Floor

Base Fabric: 22oz Vinyl ; 40oz Vinyl ; AB500 (50oz High-tear)

Wear Pleats (Seals Only), Exposure: 4" ; 8" ; 16"

Wear Pleat Fabric: 40oz Vinyl ; AB500 (50oz High-tear) ; Other _____

Inside Half-wrap (Seals Only), Up Approx. 48"

Fabric: 22oz Vinyl ; 40oz Vinyl ; 50oz AB500, High-tear ; Other _____

Fabric Color (all components): Black ; Brown ; Blue ; Green ; Other, specify _____

(Note: Some fabrics not available in all colors – Call for details, special color options)

Side Frame Cover (Shelters Only): 32oz White Flexible Vinyl ; 6oz Translucent Fiberglass

Metal Hoods: Projection: 18"; 24"; 36"; Special ___"; Width: 10' (standard); Other ___'

Finish: Galvanized (Standard) ; Painted