

ABC DOCKS

Aaron-Bradley™ Hydraulic Levelers

All Models - Standard Features - See Back for Options & Accessories

- Standard deck sizes, pit depths & dimensional requirements. *(Custom sizes available, consult factory.)*
- Clean Frame Design: 'DH' and 'LHD' Series
- Deck & Lip: High Strength Safety Tread Plate
- Service range: Up to +/- 12" from dock height
- Quiet hydraulic operation-No lifting required
- Automatic lip extension
- Lip keepers provide night lock security and cross traffic support
- Below dock safety; Maintenance strut
- Four inch lateral tilt for out of level trucks *(Fixed rear hinge on 'H' series)*
- Full width, one-piece lip hinge pin *(2-piece on 'LHD' series)*
- Full operating range toe guards; welded design for maximum strength



'DH' Series Shown

Models: 'H' 'HD' 'HX' 'DH' 'LHD'

- **Deck Support:**
 - 'H', 'HX': Structural 'C' Channel
 - 'HD': Designed for Unique Applications: Box Beam; Structural Channel or I-beam *(Note: Depending on capacity and / or specifications)*
 - 'DH':
 - Rolled 'C' Channel: 25-30,000 lbs. capacity
 - Structural 'C' Channel: 35-40,000 lbs. capacity
 - Structural 'C' Channel & I-beam: 45-60,000 lbs. capacity
 - 'LHD':
 - Rolled 'C' Channel: 25-35,000 lbs. capacity
 - Structural 'C' Channel: 40,000 lbs. capacity
- **Standard Bumpers:** 4" x 10" x 12" Laminated: 'H' and 'HX' Series; 'HD' Series: As specified / required; 4.5" x 10" x 14" Laminated: 'DH', 'LHD' Series



**Specializing in Dock Equipment
High Speed Doors & Scissor Tables**

ABC DOCKS



Aaron-Bradley™ Hydraulic Levelers

Options

- Lip Length: 18", 20"
- Weather Seals - Brush or Rubber
- Foam Insulation
- Abrasive Surface
- Molded Bumpers
- Barrier Safety Lip (*Not available on 'H' series*)
- 3 Wheel Forklift Reinforcement (*Standard on 'DH' series 35-60,000 lbs. and 'LHD' series 40,000 lbs. capacities*)
- Finishes: Abrasive Surface, Hot Dip & Cold Spray Galvanized

Accessories

- Curb Angle Kit
- Deep Pit Kit
- 'EZ' Pan—Side and Rear Panels w/ Front Curb Angle (*Assembled on Job Site*)
- Self-forming Pan w/ Leveler Welded In
- Free-Standing Frame

** Note: Options and accessories are not available with all series, call for further details.*

Architectural Specifications

- Dock leveler (s) to be Aaron-Bradley™ Model _____. Standard unit to be ____" Wide x ____" Long. Unit to be hydraulic with continuous hinged lip and header plate design. Deck and lip to be 55,000 lbs. minimum yield steel tread plate.
- Deck support beam to be: () Formed Beam or Channel; () Structural 'C' Channel; () Structural 'I' beam'.
- Lip to be ____" Long and extended ____" beyond bumpers. Rollover and cross traffic capacity to be _____lbs. Leveler to automatically raise and extend lip when control button is activated. With lip extended, leveler lowers to the floor of the trailer.
- Leveler may be recycled and stored while truck is in position at dock.
- Levelers shall meet or exceed the performance requirements of O.S.H.A. CS202-56 (1910-30) "Other Walking Surfaces" and ANSI/MH30.1-2007 or most current revision / publications in effect.

Warranty

- Starts from date of shipment - One (1) year standard on all units, unless otherwise noted.
- Option: ABC Docks will match any competitor's documented warranty for comparable products.

ABC Docks, LLC
P.O. Box 1028
Franklin, TN 37065-1028
Ph) 800-394-5944 / 615-807-1141
Fax) 615-807-1752
Web: www.aaronbradley.com
Email: sales@abcdocks.com

Distributed By:

**Specializing in Dock Equipment
High Speed Doors & Scissor Tables**