

## **LoadMaster™**

The Hydraulic Dock Leveler that is a full 9' wide, will lower 12" below dock to provide fast, efficient access to low trailers. In addition, the 7' wide main deck will service trailers 12" above dock.

The LoadMaster™ will also function as a standard dock leveler, but is especially designed to service the loading and unloading of trailers below dock height.



## **Features**

- Designed with a 9' wide deck surface for efficiently servicing low trailers, the LoadMaster™ will also service over-the-road (OTR) trailers and box trucks with special or standard heights
- Expands the width of traffic aisle at the loading zone to 9' wide
- On-board, steel-faced bumpers, raise or lower in tandem, with the leveler, to provide an adjustable height contact target for the docking trailer
- Bumpers can be lowered after the trailer docks, eliminating the common floor level bumpers associated with the typical dock leveler installation. Movement can stop at any point within the operating range to better serve the full width of the trailer
- Safe and expedited handling of palletized loads with full width pallets, side by side pallets or double stacked pallets
- Side extensions (wings) of leveler platform are synchronized with a single push-button control, which allows positioning of bumpers at the 'optimum' height for load handling. Both (wings) are operated with one cylinder and one control button
- Heavy-duty construction accommodates high-capacity/high-traffic load requirements
- Life of the LoadMaster™ is maximized by using a double-acting, regenerative hydraulic system equipped with a single hydraulic motor/pump providing power to all components
- Direct push-button control with no selector switches allows precise positioning in less time than conventional dock levelers.



## Standard Specifications

- Main Deck Size: 7' 0" W x ( ) 8' 0" L ( ) 10' 0" L ( ) 12' 0" L
- Wing Deck Size: 2 each, 1' 0" W
- Full Deck Surface, Overall Width: 9' 0"
- Capacity (lbs.): 30,000 to 100,000
- Full Hydraulic Operation
- Power-pack: Fully enclosed, regenerative system, 208v-480v/3ph/1.5hp/60Hz
- Control: Standard Push-button with NEMA 12 enclosure
- Service Range, Above/Below Dock - 8' L Unit: 12" above 12" below
- Service Range, Above/Below Dock - 10' L Unit: 15" above 12" below
- Service Range, Above/Below Dock - 12' L Unit: 18" above 12" below
- Lip: Standard 20" L provides 14" reach (lip purchase) past 6" Bumpers
- Vertical Laminated, Steel Face Dock Bumpers 6" Deep x 20" Long x 11" Wide
- Finish: Industrial Gray Enamel w/ Safety Yellow Side Striping

## Options

- Custom designed sizes and capacities: Call for details
- Application Engineering assistance and Consultation
- Combination Control Panel: Provides operation of LoadMaster™ with an ATR-700 automatic trailer restraint, overhead door, dock light or fan/heater. Can also be equipped with an auxiliary power outlet
- Finish: Custom Paint (requires mfg and paint number); Spray Metalized (Cold-spray Galvanizing)
- Lip Length Up to 24" provides 18" reach (lip purchase) past 6" Bumpers
- Vertical Laminated, Steel Face Dock Bumpers: 24" or 36" Long

**ABC Docks, LLC**  
P.O. Box 1028  
Franklin, TN 37065-1028  
Ph) 800-394-5944 / 615-807-1141  
Fax) 615-807-1752  
Web: [www.aaronbradley.com](http://www.aaronbradley.com)  
Email: [sales@abcdocks.com](mailto:sales@abcdocks.com)

**Distributed By:**



**Specializing in Dock Equipment  
& Scissor Tables**

Form 150501-LoadMaster REV0